

wedi *Foot bath*

- Ready-for-assembly foot bath
- For direct tiling
- Incl. drainage



General product description

the wedi Foot bath is an individual, tileable element that is pre-fabricated to the customer's specification.

Applications

For private and commercial use indoors with a direct load from tap and cleaning water.

Product properties

- Waterproof
- Heat insulating
- Stable and lightweight

Surface requirements

The floor must have a sufficient load capacity and must be even.

Processing

Information on processing and surface requirements can be found in the wedi "Building materials" brochure and the fitting instructions (see www.wedi.de).

Technical properties – Rigid foam

Extruded polystyrene rigid foam core	XPS
Long-term compressive strength (50 years) $\leq 2\%$ compression DIN EN 1606	0.08 N/mm ²
Compressive resistance at 10% compression EN 826	0.25 N/mm ²
Thermal conductivity EN 13164	0.036 W/mK
Bulk density EN 1602	32 kg/m ³
Temperature limits	-50°C / +75°C
Fire behaviour DIN 4102	B1
Fire behaviour EN 13501	E

Drain and overflow fittings

Sealed, built-in drain and overflow fittings

Overflow capacity	up to 0.25 l/s ; 15.0 l/min
Drain capacity	up to 0.42 l/s; 25.2 l/min
Water level	max. 250 mm

Packing

- Foot bath element to customer's specification, taking account of the water level
- Drain and overflow fittings with outlet supports DN 40/50
- Bowden cable with rotary button
- Substructure element
- Cover Fundo Fino 95 x 95 x 8 mm

Storage

wedi Foot baths should be stored such that they are protected from external mechanical loads.

Safety notice

none