

wedi Tools® | Cut-resistant tape

- Self-adhesive
- Cut & stab resistant
- Water-resistant & rot-proof
- For the protection of sealing
- Tested at the highest level in accordance with EN 388



General product description

wedi Tools cut-resistant tape is made of high-quality zirconium corundum which is applied to a flexible Y polyester mesh carrier material. The tape has a self-adhesive strip for secure fixing.

Applications

- For walls and floors
- Prevents destruction of the sealing when cutting out elastic sealants, e.g. with a cutter knife
- Suitable for all types of expansion and contraction joints
- For wall/wall joints, wall/floor joints including expansion and contraction joints in the floor
- Perfect for use with wedi Tools sealing tapes and wedi Tools butyl tub sealing tape

Processing

The surface must be free from dust, dirt, oil, grease, condensation and loose particles.

The wedi Tools cut-resistant tape is adhered in the sealing tape or sealing corner area, on the fully cured composite sealant, with the self-adhesive strip.

When used with wedi Tools butyl bathtub sealing tape, the cut-resistant tape is placed behind the edge of the bathtub with the help of the self-adhesive tape and applied directly to the butyl sealing tape. It is then sealed with a suitable wedi sealant.

Care should be taken during tile laying to ensure that the tiles are laid correctly in relation to the position of the wedi Tools cut-resistant tape in order to optimally protect the sealing.

Technical properties of cut-resistant tape

Type	High-quality zirconium corundum
Colour	green
Material thickness	0,90 mm
Length	10 m
Width	35 mm
Processing temperature	5 °C to 40 °C

Packing

10 m roll, individually packaged

Storage

Store in a cool, dry place and protect from sunlight.

Safety notice

none