

Fundo Riolito Discreto

- Attachment element for Fundo Riolito floor elements
- For the creation of an attractive wall drain
- High-quality, two-sided cover included
- Simple to clean
- 100% waterproof to the core



General product description

Attachment element for Riolito to create a wall drain solution.

Areas of application

The areas of application described apply in conjunction with the application of a wedi Fundo Riolito floor element

- In private residential construction
- In public buildings complying with DIN 18040 part 1
- In accessible dwellings complying with DIN 18040 part 2 (note specifications for minimum tile size if wheelchair access is planned, see technical specifications)
- As a construction seal combined with tile and natural stone coverings of load class A0 and A (directly loaded walls and floors in rooms in which tap or cleaning water is used very frequently or for long periods), more info available at www.wedi.eu

Product characteristics

With Fundo Riolito Discreto, the Riolito's channel can be installed into existing walls, into front wall installations and other structures such as seating, storage spaces and steps. This means that a wall-level drainage system can be created. The Fundo Riolito Discreto element can also be shortened. The system includes: A plastic moulded part integrated into a wedi building board and precisely aligned with the Riolito channel which can easily be built on top of.

Surface requirements, processing

The substrate must be a Riolito element. Please read the assembly instructions for more information concerning process (www.wedi.eu).

Technical data sheet



Technical specifications

Cover made from V_2A stainless steel, two-sided application (one side brushed surface and the other side tileable). Able to be adjusted to a tile size of between 5 and 20mm (wall and floor). Alignment is carried out simply using a template (included in delivery). Total width of element same as width of Riolito element.

Distance from floor tile to cover	7 mm
Cover dimensions (length x height x thickness)	690 x 70 x 20 mm
	790 x 70 x 20 mm
	890 x 70 x 20 mm
Horizontal installation height	150 mm
Installation height on Riolito	180 mm
	(able to be reduced
	to 150mm)

Name	Length x height x thickness	Channel length
Fundo Riolito Discreto, attachment element	800 x 180 x 76 mm	700 mm ①
Fundo Riolito Discreto, attachment element	900 x 180 x 76 mm	800 mm ②
Fundo Riolito Discreto, attachment element	1000 x 180 x 76 mm	900 mm ③
Name	Length x width x thickness	Channel length
Fundo Riolito, floor element	900 x 800 x 50 mm	700 mm ①
Fundo Riolito, floor element	1200 x 800 x 50 mm	700 mm ①
Fundo Riolito, floor element	900 x 900 x 50 mm	800 mm @
Fundo Riolito, floor element	1200 x 900 x 50 mm	800 mm @
Fundo Riolito, floor element	900 x 1000 x 50 mm	900 mm ③
Fundo Riolito, floor element	1200 x 1000 x 50 mm	900 mm ③

 $oxed{i}$ • The numbers oxdot, oxdot and oxdot signify the matching combinations with Fundo Riolito.

wedi Fundo floor elements can be shortened on site, but the geometry of the elements should be maintained.

Packaging

1 box

Scope of delivery

Fundo Riolito Discreto element incl. 1 cartridge of wedi 610, screws and hooked plates, alignment template, stainless steel cover, assembly instructions, Allen key.

Safety notice

None